



COMPRESORES ESTACIONARIOS SERIE IMCO Uso Industrial



CARACTERÍSTICAS / MODELO	MOTOR 400 V - T	DEPÓSITO LT	PRESIÓN ATMS	DESPLAZAMIENTO L.P.M.	R.P.M.	PESO KG	DIMENSIONES CM
IMCO 5/270-T	5,5 HP	270	8/10	690	1080	150	50x101x150
IMCO 7/270-T	7,5 HP	270	8/10	847	1190	159	50x105x150
IMCO 7/500-T	7,5 HP	500	8/10	847	1190	270	60x115x198
IMCO 7/500-T-AU *	7,5 HP	500	8/10	847	1190	270	60x115x198
IMCO 10/500-T	10 HP	500	8/10	1210	1080	398	60x123x198
ICMO 10/500-T-AU *	10 HP	500	8/10	1210	1080	398	60x123x198

15 ATMS – Especial Automoción

CARACTERÍSTICAS / MODELO	MOTOR 400 V - T	DEPÓSITO LT	PRESIÓN ATMS	DESPLAZAMIENTO L.P.M.	R.P.M.	PESO KG	DIMENSIONES CM
IMCO 5/270-T-AP	5,5 HP	270	12/15	576	1100	170	50x101x150
IMCO 7,5/500-T-AP	7,5 HP	500	12/15	765	1100	305	60x115x198
IMCO 10/500-T-PA	10 HP	500	12/15	1125	1100	345	60x123x198
ICMO 10/500-T-AP-AU *	10 HP	500	12/15	1125	1100	345	60x123x198

* Modelo con arrancador estrella - triángulo