



SECADORES DE AIRE SERIE Dry air MTED



MODELO	L.P.M	ALIMENTACIÓN	PESO kg	Rosca Salida Entrada	DIMENSIONES mm		
					Alto	Largo	Fondo
AIR MTED – 9	900	230V – 50 Hz	38,5	½"	510	530	300
AIR MTED – 18	1800	230V – 50 Hz	64,5	¾"	750	650	370
AIR MTED – 25	2500	230V – 50 Hz	66,5	¾"	750	650	370
AIR MTED – 32	3200	230V – 50 Hz	79,5	1"	750	650	370
AIR MTED – 38	3800	230V – 50 Hz	79,5	1"	750	650	370
AIR MTED – 49	4900	230V – 50 Hz	103	1"	850	780	370



SECADORES DE AIRE SERIE Dry air ED



MODELO	L.P.M	ALIMENTACIÓN	PESO kg	Rosca Salida Entrada	DIMENSIONES mm		
					Alto	Largo	Fondo
AIR ED – 6	600	230V / 50-60 Hz	25	½"	370	515	475
AIR ED – 9	900	230V / 50-60 Hz	26	½"	370	515	475
AIR ED – 12	1200	230V / 50-60 Hz	28	½"	370	515	475
AIR ED – 18	1800	230V / 50-60 Hz	32	½"	370	515	475
AIR ED – 25	2500	230V / 50-60 Hz	34	1"	345	445	740
AIR ED – 32	3200	230V / 50 Hz	39	1 ¼"	345	445	740
AIR ED – 43	4300	230V / 50 Hz	40	1 ¼"	345	445	740
AIR ED – 52	5200	230V / 50 Hz	41	1 ¼"	345	445	740
AIR ED – 61	6100	230V / 50 Hz	54	1 ½"	555	580	885
AIR ED – 75	7500	230V / 50 Hz	56	1 ½"	555	580	885
AIR ED – 105	10500	230V / 50 Hz	94	2"	555	625	975
AIR ED – 130	13000	230V / 50 Hz	96	2"	555	625	975
AIR ED – 168	16800	230V / 50 Hz	144	2 ½"	665	725	1105